

Terminal Tractor/Yard Spotter

Used Yard Spotter Fullerton - Tow tractors, sometimes call towing tractors or tow tugs, are vehicles used in transporting loads horizontally in warehouses, manufacturing plants, airports, arenas and other large facilities. Tow tractors are responsible for moving multiple trailers in a train. Certain tow tractors can transport helicopters and giant airplanes for the purpose of positioning inside and outside airport hangars and terminals. The tractive effort concept is how loads move from place to place. The complete amount of traction a vehicle utilizes on the ground. The heavier the load is, the more tractive effort is needed. Based on this principle, the tow tractor works by lifting a part of the load it is towing while making sure the load's wheels remain on the ground. The hydraulic mast on the tow tractor is responsible for lifting the load. It produces downforce on the drive wheel underneath to increase the tractive effort. The tow tractor is capable of transporting very heavy and large loads thanks to the traction it provides. Types of Tow Tractors Heavy-duty tow tractors and load carriers are two types of tow tractors. Load Carriers Industries such as e-commerce, manufacturing, and airport baggage and parcel systems must regularly move many individual and varying sized items to or from a single location. Tow tugs and load carriers easily transport single items that have been deposited on wheeled platforms and move them with ease. These load carrier tow tractors fall under the material handling equipment industry which includes other machines such as pallet jacks, forklifts and cranes. Load carrier tow tugs transport loads at ground level only, rather than lifting or lowering off the ground or from shelving or other hard to reach areas. This means that the load has already been on wheels or placed on a wheeled platform before transport. Wheeled platforms are called skates, trolleys and bogies. The tow tractor attaches to the trolley and operates similarly to how train cars are attached to a locomotive. Typically, the tow tug features a steel coupling male-end that attaches to a female-end on the trolley's front. The back of the trolley has a male-end steel coupling that can then be used to attach multiple trolleys onto a single tow tug, transporting all the trolleys in a train-like formation. These machines can transport a variety of items in varying conditions. Trolley types differ to provide customization options. Many trolleys can be connected since they are compatible with one another. Different kinds of trolleys can be maneuvered in a single train, creating flexible transport options. An additional benefit of operating with load carrier tow tractors as opposed to forklifts is the unobstructed view offered by a tow tractor, increasing the safety of work areas. Load carrier tow tractors transport trolleys in a forward direction which decreases the safety concerns common with reverse forklift operations. This design is excellent for locations that have a high level of safety such as manufacturing locations and airports. Towing many items at once saves time and money compared to relying on forklifts to move single things. Tugs are easy to move and safe to use. One benefit of these tow tugs is that an operator usually does not require a license. No license is necessary since these units do not lift loads up from the ground like cranes, and forklifts that require licensing. Three subtypes of load carrier tow tractors include rider-seated, stand-in and pedestrian. Pedestrian Tow Tractors A pedestrian tow tractor, also referred to as an electric tug, electric tugger, electric hand tug or tow tractor, is a walk-behind machine designed for easy movement of wheeled loads. These compact machines are simple to use and can maneuver easily. Stand-in Tow Tractors The most common design for businesses that rely on horizontal manufacturing transport and order picking are stand-in tow tractors. These units deliver a secure driver platform and deliver a smaller footprint compared to the rider-seated models. Rider-Seated Tow Tractors The rider-seated tow tractors are similar to the stand-in tow tractors with the exception they provide a seated platform for the driver. These models are commonly used for transporting loads over farther distances such as moving checked baggage from the airport check-in to the aircraft at the terminal. Rider fatigue is decreased with sit-down units for more efficiency and productivity. Heavy Duty Tow Tractors In the aviation industry, large passenger and cargo planes usually employ the concept of pushback. Pushback is the process of pushing an aircraft back from the terminal by means not originating from the aircraft's

personal power. Pushback is achieved by employing pushback tugs or pushback tractors. Pushback tugs feature a low-profile enabling them to travel under the aircraft's nose for easy attachment. Since the aircraft weight is heavy, these units need to be heavy in order to retain adequate ground friction to move the aircraft. A typical tractor for large aircraft weighs up to 54 tons. They usually have a driver's cab that can be raised and lowered to increase visibility when reversing. The pushback tow tractor and pushback tug are also employed when taxiing the aircraft is not an option. They are commonly used to move the machine into and outside of aircraft maintenance hangars. The two subtypes of pushback tow tractors include conventional tow tractors and towbarless tow tractors. Conventional Pushback Tow Tractors Conventional units rely on a tow bar to connect the tug to the aircraft's nose landing gear. Laterally attached to the nose landing gear, the tow tractor can make certain slight vertical height adjustments if needed. The tow bar that attaches to the tug can pivot vertically and laterally. Acting like a giant lever, the tow bar can rotate the nose landing gear. Every aircraft has a special tow fitting and the towbar functions as an adapter between the fitting on the landing gear and the standard-sized tow pin. Heavy towbars have their own wheels for big aircraft and can ride on these wheels when disconnected from planes. The hydraulic jacking mechanism is attached to the wheels, allowing the towbar to lift to the correct height in order to mate with the tug and the aircraft. The same means are used in reverse during the pushback process to raise the towbar wheels from the ground. The towbar is capable of being connected at the tractor's rear or front, depending on if the machine needs to be pulled or pushed. Depending on whether the aircraft needs to be pushed or pulled, the towbar can be attached to the front or rear of the tractor. Towbarless Pushback Tow Tractors Towbarless tractors, as their name suggests, don't rely on a towbar. Instead, these machines scoop up the nose landing gear to lift it off of the ground so the tug can move the plane. This allows better control of the aircraft and higher speeds; it may also eliminate the need to have a worker in the cockpit to apply the aircraft's brakes. As there is no need to maintain numerous towbars, simplicity is the main advantage of this unit. By connecting the tug directly to the aircraft's landing gear tug operators have better control and responsiveness when maneuvering.